


**NASA TECHNICAL
MEMORANDUM**

NASA TM X-2369



NASA TM X-2369

C.1

**LOAN COPY: RETURN
AFWL (DO 4L)
KIRTLAND AFB, N. I.**

0034784



TECH LIBRARY KAFB, NM

**EVALUATION OF ION DENSITY
AND PLASMA POTENTIAL
FROM LANGMUIR PROBE DATA**

by Roman Krawec

Lewis Research Center

Cleveland, Ohio 44135



0034784

1. Report No. NASA TM X-2369		2. Government Accession No.		3. Recipient	
4. Title and Subtitle EVALUATION OF ION DENSITY AND PLASMA POTENTIAL FROM LANGMUIR PROBE DATA				5. Report Date September 1971	
				6. Performing Organization Code	
7. Author(s) by Roman Krawec				8. Performing Organization Report No. E-6401	
9. Performing Organization Name and Address Lewis Research Center National Aeronautics and Space Administration Cleveland, Ohio 44135				10. Work Unit No. 129-02	
				11. Contract or Grant No.	
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, D.C. 20546				13. Type of Report and Period Covered Technical Memorandum	
				14. Sponsoring Agency Code	
15. Supplementary Notes					
16. Abstract <p>The collisionless probe theory of Laframboise is used to calculate values of probe current for a plasma composed of electrons and ions with equal temperatures and Maxwellian velocity distribution functions. Specifically, the value of probe current is given as a function of ion density for a probe biased at a voltage $5kT/q$ below probe floating potential, where k is Boltzmann's constant, T is temperature, and q is the electron charge.</p>					
17. Key Words (Suggested by Author(s)) Langmuir probes Plasma diagnostics Plasma density Ion currents				18. Distribution Statement Unclassified - unlimited	
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of Pages 25	
				22. Price* \$3.00	

EVALUATION OF ION DENSITY AND PLASMA POTENTIAL FROM LANGMUIR PROBE DATA

by Roman Krawec
Lewis Research Center

SUMMARY

The collisionless probe theory of Laframboise is used to calculate values of probe current for a plasma composed of electrons and ions with equal temperatures and Maxwellian velocity distribution functions. Specifically, the value of probe current is given as a function of ion density for a probe biased at a voltage $5kT/q$ below probe floating potential, where k is Boltzmann's constant, T is temperature, and q is the electron charge.

Calculations are performed for four values of probe diameter and cover the density and temperature regions from 10^9 to 10^{14} cm^{-3} and 1 to 30 eV, respectively. Ion masses from 1 to 4 are considered.

INTRODUCTION

Although the problem of ion collection by a cylindrical probe in a collisionless plasma has been solved exactly by Laframboise (ref. 1), the manner in which the results are presented is inconvenient for use by the experimenter. Attempts at simplifying the data analysis have recently been made by Corbin and Oss (ref. 2) and by Battle and Bell (ref. 3). Corbin and Oss compute complete probe current-voltage characteristics for a low-density cesium plasma at three electron temperatures and for two different probes. These calculations were performed for an extremely restricted range of parameters and thus cannot be used by most experimenters. A further problem lies in the fact that any attempt to plot complete current-voltage characteristics for a wide range of parameters would lead to an undesirably large number of figures.

The work of Battle and Bell, on the other hand, is presented in the form of dimensionless parameters for helium and argon. These are given as figures 2 and 3 of reference 3 and cover a wide region of ratios of probe radius to Debye length. However, their

work does not apply to a hydrogen plasma.

The results of Laframboise are presented in this report in a form which should be useful to the experimenter. The data are presented in the form of probe current per unit length as functions of ion density for cylindrical probes of various diameters biased $5kT/q$ below floating potential, where k is Boltzmann's constant, T is temperature, and q is the electron charge. The choice of $5kT/q$ below floating potential is arbitrary; it was chosen to be sufficiently far from plasma potential so that the probe would operate in a region where the electron current is negligible. The electron temperature is assumed to be available from other probe measurements.

The ranges of plasma parameters covered are (1) electron temperature, 1 to 30 eV; (2) ion number density, 10^9 to 10^{14} cm^{-3} ; (3) ion mass, 1 to 4; and (4) probe radius, 0.0127 to 0.0318 cm (radius from 0.005 to 0.0125 in. in steps of 0.0025 in.).

Although the calculations were performed for a plasma with equal electron and ion temperatures ($T_e = T_i$), the use of the results for $T_i \leq T_e$ is justified by the weak dependence of ion current on ion temperature.

RELATIONS USED IN THE CALCULATIONS

The total current to the probe is given (ref. 2) as

$$I_p = I_e + I_i = -I_{se} \exp\left(-\frac{qV}{kT}\right) + I_i$$

$$= 2\pi RLqn\sqrt{\frac{kT}{2\pi M}} \left[\psi(\varphi, \beta) - \sqrt{\frac{M}{m}} \exp(-\varphi) \right] \quad (\text{SI units}) \quad (1a)$$

where

I_p probe current

I_e electron current

I_i ion current

I_{se} saturation electron current

q electron charge

V probe potential measured with respect to plasma potential

k Boltzmann's constant

T temperature

R	probe radius
L	probe length
n	ion number density
M	ion mass
ψ	ratio of ion current at given probe potential to ion current at plasma potential
$\psi(\varphi, \beta)$	dimensionless ion current calculated by Laframboise
φ	dimensionless probe potential, qV/kT
β	dimensionless probe radius, R/λ_d
R	probe radius
λ_d	Debye length
m	electron mass

The probe current per unit length is

$$\frac{I_p}{L} = 3.91 \times 10^{-13} \frac{nRT^{1/2}}{Z^{1/2}} \left[\psi(\varphi, \beta) - 42.8 Z^{1/2} \exp(-\varphi) \right] \quad (\text{A/cm}) \quad (1b)$$

where Z is the atomic number of the ion, and temperature is in eV, ion number density is in cm^{-3} , and probe radius and length are in cm. Values of $\psi(\varphi, \beta)$ are presented in table I, which was taken from reference 2.

RESULTS AND DISCUSSION

The value of φ at which I_p equalled zero (eq. (1b)) was found for given values of n , T , and Z by using an iteration procedure. (This is the probe floating potential, denoted by φ_0 .) The value of probe current at $\varphi = \varphi_0 + 5$ was then calculated. Values of $\psi(\varphi, \beta)$ for values of β other than those given in table I were extrapolated by fitting a parabola through three points in the immediate vicinity of the desired value of β .

The Debye length is given as

$$\lambda_d = 785 \sqrt{\frac{T}{n}} \quad \text{cm}$$

where the temperature is expressed in eV and the number density in cm^{-3} .

The calculations are limited to values of n and T such that $1 \leq \beta \leq 50$ in order to stay within regions of validity of the theory. The limitations imposed on the density for a given temperature by these restrictions are presented in figure 1. Figure 1(a) presents the minimum densities for which the calculations are valid as a function of probe radius and particle temperature, while figure 1(b) presents the maximum densities.

Figures 2 to 5 present the probe currents at $\phi = \phi_0 + 5$ for various probe radii and ion masses as functions of temperature and density.

With the solution of equation (1b) used for ϕ_0 , the plasma potential can be obtained in terms of the floating potential. Figure 6 gives the value of the dimensionless probe floating potential for different plasma conditions.

As an example of how the curves are to be used, assume an atomic hydrogen plasma and the following: probe radius, 0.0254 cm; probe length, 0.1 cm; electron temperature, 8 eV; and probe floating potential, -20 V.

The atomic hydrogen plasma ($Z = 1$) and the probe radius tell us that figure 2(c) is the proper one to use. The first thing to do is to measure the probe current when the probe is biased at -60 V (five times the electron temperature or 40 V below floating potential).

If this probe current is 9 mA, the probe current per cm would then be 90 mA. Referring to figure 2(c), 90 mA at a temperature of 8 eV corresponds to a number density of $1.35 \times 10^{12} \text{ cm}^{-3}$.

Furthermore, figure 6(c) tells us that under these conditions the dimensionless floating potential is near 3.1, which means that the plasma potential is 3.1×8 above the probe floating potential. The plasma potential in this case is thus 4.8 V.

Lewis Research Center,

National Aeronautics and Space Administration,

Cleveland, Ohio, June 17, 1971,

129-02.

REFERENCES

1. Laframboise, James G.: Theory of Spherical and Cylindrical Langmuir Probes in a Collisionless, Maxwellian Plasma at Rest. Rep. 100, Univ. Toronto, Inst. Aerospace Studies, June 1966. (Available from DDC as AD-634596.)
2. Corbin, John C., Jr.; and Oss, John P.: Langmuir Probe Curves for Alkali Metal Magnetoplasmas. Rep. ARL-69-0108, Aerospace Res. Labs., Wright-Patterson AFB, July 1969. (Available from DDC as AD-695054.)
3. Battle, E. L.; and Bell, R. B.: Reducing Experimental Langmuir Probe Data to Obtain a Comparison with Collisionless Probe Theory. Phys. Fluids, vol. 13, no. 6, June 1970, pp. 1488-1491.

TABLE I. - DIMENSIONLESS ION CURRENT FOR A CYLINDRICAL PROBE WHERE ION AND ELECTRON TEMPERATURES ARE EQUAL AND BOTH SPECIES ARE MAXWELLIAN

[Data from ref. 2.]

Dimensionless probe potential, φ	Dimensionless probe radius, β									
	1	1.5	2	2.5	3	4	5	10	20	50
	Dimensionless ion current, $\psi(\varphi, \beta)$									
0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
.1	1.0804	1.0804	1.0804	1.0804	1.0804	1.0804	1.0804	1.0803	1.0803	1.0803
.3	1.2101	1.2101	1.2101	1.2101	1.2101	1.2101	1.2100	1.208	1.205	1.198
.6	1.3721	1.3721	1.3721	1.3721	1.3721	1.3721	1.371	1.362	1.348	1.327
1.0	1.5560	1.5560	1.5560	1.5560	1.5560	1.554	1.549	1.523	1.486	1.439
1.5	1.7551	1.7551	1.7551	1.7551	1.754	1.747	1.735	1.677	1.605	1.523
2.0	1.9320	1.9320	1.9320	1.9320	1.928	1.913	1.893	1.798	1.689	1.576
3.0	2.2417	2.2417	2.2417	2.237	2.226	2.192	2.151	1.98	1.801	1.638
5.0	2.7555	2.7555	2.731	2.731	2.701	2.626	2.544	2.22	1.940	1.703
7.5	3.2846	3.2846	3.266	3.227	3.174	3.050	2.920	2.442	2.060	1.756
10.0	3.7388	3.7388	3.735	3.703	3.645	3.567	3.402	3.231	2.622	1.798







Figure 1. - Region of validity - minimum and maximum densities to be measured.




(a) Probe radius, 0.0127 cm (0.005 in.).

Figure 2. - Probe ion currents for mass 1 ions at probe potential $\varphi = \varphi_0 + 5$.




(b) Probe radius, 0.01905 cm (0.0075 in.)

Figure 2. - Continued.




(c) Probe radius, 0.0254 cm (0.010 in.).

Figure 2. - Continued.




(d) Probe radius, 0.0318 cm (0.0125 in.).

Figure 2. - Concluded.




(a) Probe radius, 0.0127 cm (0.005 in.).

Figure 3. - Probe current for mass 2 ions at probe potential $\psi = \psi_0 + 5$.




(b) Probe radius, 0.01905 cm (0.0075 in.)

Figure 3. - Continued.




(c) Probe radius, 0.0254 cm (0.010 in.).

Figure 3. - Continued.




(d) Probe radius, 0.0318 cm (0.0125 in.).

Figure 3. - Concluded.




(a) Probe radius, 0.0127 cm (0.005 in.).

Figure 4. - Probe current for mass 3 ions at probe potential $\phi = \phi_0 + 5$.




(b) Probe radius, 0.01905 cm (0.0075 in.).

Figure 4. - Continued.



(c) Probe radius, 0.0254 cm (0.010 in.).

Figure 4. - Continued.



(d) Probe radius, 0.0318 cm (0.0125 in.).

Figure 4. - Concluded.




Figure 5. - Probe current for mass 4 ions at probe potential $\varphi = \varphi_0 + 5$.






Figure 5. - Continued.




(c) Probe radius, 0.0254 cm (0.010 in.)

Figure 5. - Continued.




(d) Probe radius, 0.0318 cm (0.0125 in.).

Figure 5. - Concluded.




(b) Probe radius, 0.01905 cm (0.0075 in.).

Figure 6. - Probe floating potential.



(c) Probe radius, 0.0254 cm (0.010 in.).



(d) Probe radius, 0.0318 cm (0.0125 in.).

Figure 6. - Concluded.


OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

FIRST CLASS MAIL

POSTAGE AND FEES PAID
NATIONAL AERONAUTICS AND
SPACE ADMINISTRATION



013B 01 C2 UL 25 710910 S00903DS 720401
DEPT OF THE AIR FORCE
AF SYSTEMS COMMAND
AF WEAPONS LAB (WLOL)
ATTN: E LOU BOWMAN, CHIEF TECH LIBRARY
KIRTLAND AFB NM 87117



POSTMASTER: If Undeliverable (Section 158
Postal Manual) Do Not Return

"The aeronautical and space activities of the United States shall be conducted so as to contribute . . . to the expansion of human knowledge of phenomena in the atmosphere and space. The Administration shall provide for the widest practicable and appropriate dissemination of information concerning its activities and the results thereof."

— NATIONAL AERONAUTICS AND SPACE ACT OF 1958

NASA SCIENTIFIC AND TECHNICAL PUBLICATIONS

TECHNICAL REPORTS: Scientific and technical information considered important, complete, and a lasting contribution to existing knowledge.

TECHNICAL NOTES: Information less broad in scope but nevertheless of importance as a contribution to existing knowledge.

TECHNICAL MEMORANDUMS: Information receiving limited distribution because of preliminary data, security classification, or other reasons.

CONTRACTOR REPORTS: Scientific and technical information generated under a NASA contract or grant and considered an important contribution to existing knowledge.

TECHNICAL TRANSLATIONS: Information published in a foreign language considered to merit NASA distribution in English.

SPECIAL PUBLICATIONS: Information derived from or of value to NASA activities. Publications include conference proceedings, monographs, data compilations, handbooks, sourcebooks, and special bibliographies.

TECHNOLOGY UTILIZATION PUBLICATIONS: Information on technology used by NASA that may be of particular interest in commercial and other non-aerospace applications. Publications include *Tech Briefs*, Technology Utilization Reports and Technology Surveys.

Details on the availability of these publications may be obtained from:

SCIENTIFIC AND TECHNICAL INFORMATION OFFICE
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
Washington, D.C. 20546